

AcrySeal

Sealer for protection and enhancement of concrete

Description

AcrySeal is an aromatic solvent carried dispersion of specialised acrylic resin. AcrySeal is available in clear and pigmented versions.

Uses

AcrySeal is used for the protection and dressing of concrete against staining from various liquids including oils and certain acids. **AcrySeal** prevents penetration of water into concrete and reduces slipperiness when wet.

Application

AcrySeal should only be applied to clean dry concrete. If pigmented, ensure the product is mixed well before application.

AcrySeal may be spray applied or by brush, lambs wool applicator or roller.

AcrySeal dries rapidly and therefore should be applied quickly and evenly. Ensure that areas are well ventilated and that

applicators take breaks to breathe fresh air where large areas are being treated.

The solvent in AcrySeal is flammable and no smoking or any forms of ignition should be allowed near the product or in rooms being treated. Protective wear is essential during application. Clean-up should be by laquer thinners followed by soap and water.

Packaging

Packed in 5L, or 25L fluorinated plastic cans.

Coverage

Dependant on the porosity of the substrate **AcrySeal** will cover approximately 5 to 8m² per Litre, per coat.

Shelf Life

Six months properly stored, and may need thinning if there has been loss of solvent. Stirring is necessary to re-disperse settled pigment.



Samson Technologies cc

Unit 4, Trevallyn Park East, Hyskraan Close, Kya Sands, Randburg, ZA

Tel: +27 (0)11 462 2666 **Email:** info@samson.co.za **Web:** www.samson.co.za

Warranty

Samson warrants that its products will perform as declared in its literature and this warranty extends only to the replacement of any of its products that may be proven to be defective.

Disclaimer

Samson Technologies retains the right to change any information in our literature, at any time, without prior notification.