

DecorTex

Decorative Weatherproof Coating

Based on microcrystal activated cement and flexible powdered polymers

Description

DecorTex is the modern multi-purpose long life coating. It weatherproofs and decorates walls and concrete in one easy step. **DecorTex** is a finely divided powder with pozzulanic nano particles and crystalline waterproofing added to high strength cement. **DecorTex** is a one component powder, containing powdered polymers, water is simply added on site to a paintable consistency.

Advantages

DecorTex develops the strength of hydrated Cem II/B-L 52.5R, the microcrystal activation, and a high polymer content, provides protection against the effects of water ingress. No need to overcoat or repaint the waterproofing.

DecorTex comes in a variety of decorative colours.

DecorTex is suitable for homes, apartment blocks, boundary walls, swimming pools, koi ponds, and weatherproofs grain silos and industrial structures.

DecorTex provides finely textured brush or stippled finishes, as desired.

Application

Add 8 L of water to a clean bucket. Using a paint mixing paddle on a drill, create a vortex in the water. Slowly add the **DecorTex** powder into the vortex while mixing. Continue to mix the product for one full minute to allow for activation of the chemicals.

Pre-wet the substrate to be coated.

Apply **DecorTex** to the surface to be treated using a roller or for best results a suitable paint or block brush.

Yield

2m² – 4m² per Litre depending on the condition of the substrate.

DecorGuard/Siloxane Solution

DecorGuard (water based) or **Siloxane Solution** (solvent based) are optional secondary hydrophobic induction treatments to repel water and prevent long term dirt adhesion from atmospheric pollution or mud splashing. Once the **DecorTex** is completely dried (about 48 hours) the **Siloxanes** may be sprayed onto the coating. Work wet on wet and allow the liquid to flood down the area being treated. Apply only the amount that the coating will suck in. **DecorGuard/Siloxane Solution** may be re-applied at any time, but if properly applied a single coat should provide 10 years protection.

Packaging and Storage

DecorTex is available in 20kg bags, and may be stored for up to 1 year in dry cool conditions.



Samson Technologies cc

Unit 4, Trevallyn Park East, Hyskraan Close, Kya Sands, Randburg, ZA

Tel: +27 (0)11 462 2666 **Email:** info@samson.co.za **Web:** www.samson.co.za

Warranty

Samson warrants that its products will perform as declared in its literature and this warranty extends only to the replacement of any of its products that may be proven to be defective.

Disclaimer

Samson Technologies retains the right to change any information in our literature, at any time, without prior notification.