

# ResinCure

Liquid membrane forming curing compound for concrete

## Description

**ResinCure** curing compound is sprayed onto green state concrete surfaces and produces a membrane that provides maximum moisture retention through the critical curing period. The coating dries quickly. Curing compound has often been found to be particularly important in warm winter weather where low relative humidity leads to rapid drying of concrete.

**ResinCure** is solvent and hydrocarbon resin, resin emulsion based and meets the ASTM C-309-74 specification.

## Bonding

**ResinCure** will not impair the bond of adhesive used for installing overlayment such as vinyl or tile. It is not necessary to remove **ResinCure** from concrete joints before applying sealants, (subject to manufacturers recommendations).

## Application

**ResinCure** is applied by means of a low pressure hand sprayer immediately following the final finishing operation of the concrete. **ResinCure** may be applied with a fine hair broom or roller, as soon as the surface has sufficiently hardened as to not indent or mark the surface.

## Coverage

The coverage of **ResinCure** is dependent upon the texture of the concrete surface. The coverage may vary from 6 to 8 m<sup>2</sup> / L.

Curing and sealing is accomplished in one operation. No other protective covering, such as hessian or plastic sheeting is required. Only one coat of **ResinCure** is required to cure the concrete.

**Clean-up** : Use mineral turpentine to clean tools.

## Precaution

**ResinCure** is flammable. Post "No Smoking" signs when applying **ResinCure**. Do not use near open flames or operations which may cause combustion of the product e.g. welding. Use in a well ventilated area with the appropriate PPE.

## Packaging

**ResinCure** is supplied in 5 and 25 litre jerry cans, and 200L drums.

## Storage

Protect from extreme temperatures. Store under cover. Ensure lids are tightly secured to avoid evaporation of solvent.

## Shelf Life

9 months correctly stored.



## Samson Technologies cc

Unit 4, Trevallyn Park East, Hyskraan Close, Kya Sands, Randburg, ZA

**Tel:** +27 (0)11 462 2666 **Email:** info@samson.co.za **Web:** www.samson.co.za

## Warranty

Samson warrants that its products will perform as declared in its literature and this warranty extends only to the replacement of any of its products that may be proven to be defective.

## Disclaimer

Samson Technologies retains the right to change any information in our literature, at any time, without prior notification.