

MM Sealer Combo (Modified Methacrylate)

Hydrophobic induction and pore blocking treatment for concrete or ceramics

Description

MM Sealer Combo is a solvent carried blend of methacrylate, alkylalkoxisiloxane and waxes. Clear liquid with odour of aliphatic and aromatic solvent.

Properties

MM Sealer Combo contains appropriate waxes and resins to produce a satin sheen. The silane siloxane properties render the surface hydrophobic and non-slip in wet.

MM Sealer Combo charges the surface of concrete with a powerful excess of anions, and therefore repels water on all absorptive ceramic and cement based products.

MM Sealer Combo slightly darkens treated substrates dependant on application rate chosen.

Uses

Wherever liquid, water or the ingress of aqueous solutions into concrete must be prevented. **MM Sealer Combo** induces long lasting water repellancy properties into concrete, stone or ceramic substrates (brick, tile etc). **MM Sealer Combo** resists pollution staining, and repels acid waters, thus being extremely useful in arresting carbonation of concrete and resultant reinforcing bar corrosion.

MM Sealer Combo stops the normal soiling or staining of diamond polished concrete floors, parking decks and hard-stands where easy removal of oil or grease is desired.

Application

Ensure that surface is dry before application. If applied over HC Sealer. A minimum of 24 hours should be allowed for drying before application of **MM Sealer Combo** onto cured concrete. If concrete is newly installed allow 21 to 28 days before applying **MM Sealer Combo**.

Storage

Store in cool, dry conditions. Do not use any gelled, opaque product, which is an indication of water contamination. Mix product well before use.

Packaging

MM Sealer Combo is available in 200L drums, 25 Litre and 5 Litre polycans.

Warning

Being solvent carried, all areas to be treated must be well ventilated. Avoid excessive breathing in of MM Sealer vapours and take fire preventative precautions. MM Sealer has a flash-point of 70°C



Samson Technologies cc

Unit 4, Trevallyn Park East, Hyskraan Close, Kya Sands, Randburg, ZA

Tel: +27 (0)11 462 2666 **Email:** info@samson.co.za **Web:** www.samson.co.za

Warranty

Samson warrants that its products will perform as declared in its literature and this warranty extends only to the replacement of any of its products that may be proven to be defective.

Disclaimer

Samson Technologies retains the right to change any information in our literature, at any time, without prior notification.