

TextureCoat

Decorative, cementitious semi self-levelling overlayment, with textured finish

Description

TextureCoat is modern multi-purpose overlayment for concrete floors, over coating blemishes in one easy step. Water is simply added on site to a trowelable consistency. **TextureCoat** is a course powder with quartz aggregate, pozzulanic nano particles, acrylic polymer powders, added to high strength cement.

Advantages

TextureCoat develops the strength of hydrated Cem II/B-L 52.5R, and a high polymer content, provides protection against the effects of water ingress, and gives slight flexibility to the overlayment.

TextureCoat is available in a variety of decorative colours.

TextureCoat is suitable for homes, pathways, swimming pool surrounds, apartment blocks, garage floors, offices, lodges and where ever a new fresh industrial look is needed.

TextureCoat provides finely textured finish.

Application

Add 4 to 4.5 L of water to a clean bucket. Using a paint mixing paddle on a drill, create a vortex in the water. Slowly add the **TextureCoat** powder into the vortex while mixing. Continue to mix the product for one full minute to allow for activation of the chemicals.

Pre-wet the substrate to be coated, and ensure it is free of any dust or loose particles. Apply P3 Primer as a slurry coat. While P3 Primer is still wet, apply **TextureCoat** to the surface. Spread the mixed material by notched or steel towel. For large areas application teams should be organised so that the pouring and spreading is done continuously to avoid cold joints.

Yield

Mixed with about 16 to 18 % (4 to 4.5L) water (by weight) each 25 kg of **TextureCoat** powder will yield about 12 Litres of self-levelling product, which will cover about 3 to 4 square meters at 2 to 3mm thick.

Guidelines

Ensure your surface is protected from wind and direct sunlight. Allow for minimum 24 hours cure before trafficked.

Sealers

The Samson range of **MM Sealers** is well suited to sealing and protecting **TextureCoat** being a topical coating of acrylic resin sealer.

MM Sealer Siloxane will render the surface hydrophobic, and water will bead on the surface keeping the concrete dry.

MM Sealer Combo will protect, add low sheen and give water repellency to the surface.

Packaging and Storage

TextureCoat is available in 25kg bags, and may be stored for up to 1 year in dry cool conditions.



Samson Technologies cc

Unit 4, Trevallyn Park East, Hyskraan Close, Kya Sands, Randburg, ZA

Tel: +27 (0)11 462 2666 **Email:** info@samson.co.za **Web:** www.samson.co.za

Warranty

Samson warrants that its products will perform as declared in its literature and this warranty extends only to the replacement of any of its products that may be proven to be defective.

Disclaimer

Samson Technologies retains the right to change any information in our literature, at any time, without prior notification.